

ASSEMBLED MATABROTO

LINE SPROUT REMOVAL

www.ikedamaq.com.br

MATABROTO EBT 220 M



The MATABROTO (Root Destroyer/Eradicator) cuts the soil horizontally in the whole working width with a depth that can be regulated between 20 and 40 cm. This horizontal cut destroys the root system of the majority of vegetation present in overgrow pasture and causes a complete and homogeneous loosening and aeration of the soil.

The exclusive project of Arms in Tandem allow an assembly with greater distance between them, providing minimum disturbance to soil surface, significant reduction of plug risks even in the most critical situations, and less tensile stress, allowing for fast recovery of the pastures.

Without the barrier of compaction, the roots grow vigorously towards the deepest layers of the soil where there is water even in the most lingering droughts. It increases the capacity for water infiltration, retention and storage, protecting level curves.

MATABROTO EBR 220 M

Equipped with Straight Arms, suitable for work in soils with excessive volume of superficial roots which are more prone to plugging.



45 days after Matabroto Original Pasture

Model	Type	Blades	Working Width	Security	Total Weight	Power Minimum
EBT 165 M	Assembled	3	165 cm	Shock Control	578 kg	80 hp 4x4
EBT 220 M	Assembled	4	220 cm	Shock Control	610 kg	105 hp 4x4
EBT 275 M	Assembled	5	275 cm	Shock Control	921 kg	130 hp 4x4
EBT 330 M	Assembled	6	330 cm	Shock Control	956 kg	155 hp 4x4
EBT 385 M	Assembled	7	385 cm	Shock Control	1361 kg	180 hp 4x4
EBT 440 M	Assembled	8	440 cm	Shock Control	1405 kg	205 hp 4x4
EBR 165 M	Assembled	3	165 cm	Shock Control	578 kg	80 hp 4x4
EBR 220 M	Assembled	4	220 cm	Shock Control	610 kg	105 hp 4x4
EBR 275 M	Assembled	5	275 cm	Shock Control	921 kg	130 hp 4x4
EBR 330 M	Assembled	6	330 cm	Shock Control	956 kg	155 hp 4x4
EBR 385 M	Assembled	7	385 cm	Shock Control	1361 kg	180 hp 4x4
EBR 440 M	Assembled	8	440 cm	Shock Control	1405 kg	205 hp 4x4